

# **ATLAS CRACK FILLER (GYPTEC)**

## **DESCRIPTION:**

*Gyptec*, is a gypsum-based product for filling cracks and cavities in walls. It can also be used as a skimming material to give a smooth surface prior to painting. *Gyptec* contains a cellulose derivative, which improves cohesive strength and promotes adhesion to ceiling boards, plaster, lime, cement and wood.



# **USES:**

*Gyptec* Crack filler is highly effective smooth filler for all interior applications to repair cracks & holes in plaster, brick, and wood, concrete & asbestos fiber board.

#### **FEATURES:**

- a) The product is specially formulated to produce a high compressive strength and excellent adhesion under most conditions.
- b) It mixes easily with water to a lump-free and slump resistant paste which can be toweled to a smooth finish.
- c) When mixed has a working time of 45 minutes.
- d) Filling cracks, slits, cavities and gaps on walls and woodwork

## **LIMITATIONS:**

- a) Not suitable for repairing of structural faults (foundation movements)
- b) Not suitable for the repair of small indentations (will dry too fast)
- c) Not suitable for repairing cracks on flexible

## **PRODUCT INFORMATION:**

Appearance	Free Flowing Powder
Colour	Off White
Mass Solid	100 %
Specific Gravity	2.6 (Typical)
Application Temp.	5ºC - 35ºC
Drying Time	Max. 24 Hours
Pot Life	Approx. 4 Hours

For Further Information, please contact us at:

Yemen Company for Paints & Derivatives Ltd.

Tel. +967-4-205570/72 E-mail: info@ycpd.biz



# **APPLICATION DETAILS**

## Mixing:

Add 2 parts of powder to 1 part of water (by weight). Mix until soft putty like paste is formed. Extra water can be added to achieve the correct consistency for application. Use within 45 Minutes after mixing.

#### • Method:

**Putty Knife, Trowel** 

#### • Substrate:

Masonry plasters, wood, brick, plaster board, etc.

- Surface Preparation:
- a) Open all cracks to ensure good adhesion to all surfaces.
- b) The surface to be filled must be thoroughly cleaned.

For Further Information, please contact us at:

Yemen Company for Paints & Derivatives Ltd.



Tel. +967-4-205570/72 E-mail: info@ycpd.biz